



# FieldSWing UR-3

## Speed indicator

- Modular system
- Simple and waterproof construction
- Excellent visibility range
- Minimum maintenance
- Proven design using standard bulbs as light source



### GENERAL DESCRIPTION

Speed indicator FieldSWing UR-3 (further UR-3) is an element of modular system of light signal FieldSWing AZD-70. This optical system generates the speed signal aspects.

It is mostly used for mast and cantilever types of signals. The light source consists of two rows of bulbs, each with a separate optical system including the green or yellow filter and the condenser lens.

UR-3 is designated for masts and cantilever signals in configurations with signal lamps FieldSWing NS-01 and FieldSWing LLA-2. UR-3 can be combined with other light signal elements.

### BASIC TECHNICAL DESCRIPTION

UR-3 is constructed as a waterproof lockable cabinet made of aluminum alloy with back lockable door.

As UR-3 light source the bulbs with defined light intensity, shape and filament position has been approved.

UR-3 can be assembled into light signal sets.

The electronic unit is designed to reduce the light intensity during the night operation.





## BASIC TECHNICAL PARAMETERS

Standard bulb	2 × 4 pcs. 12 V, 20 W, base BA 20d
Input	2 × 80 W
Signal light chromaticity	green, yellow
Visibility	533 m
Insulation resistance	250 MΩ
Cover rating	IP 54
Temperature range	-40 °C to +70 °C
Main dimensions including shade	600 × 304 × 700 mm
Weight	20 kg

